

Uncontrolled document as of November 19, 2010. Refer to website for up to date specifications.

# CASES 1450 Case



\*OD Green available upon request (minimum quantities apply)

## 1450 Case

- **Watertight, crushproof, and dust proof**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded handle
- Stainless steel hardware and padlock protectors
- Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- Lifetime Guarantee of Excellence

## 1450 Case Configurations

Cat. #	Description
1450	1450 Case
1450NF	1450 Case (No foam)
1454	1450 Case with Padded Dividers

## 1450 Case Specifications

### Exterior Dimensions (L x W x D)

16.00" x 13.00" x 6.87" (40.6 x 33 x 17.4 cm)

### Lid Depth

1.75" (4.4 cm)

### Weight with foam

6.39 lbs. (2.9 kg)

### Range Temperature

-40 / 210° F  
(-40 / 99° C)

### Interior Dimensions (L x W x D)

14.62" x 10.18" x 6.00" (37.1 x 25.8 x 15.2 cm)

### Bottom Depth

4.25" (10.8 cm)

### Weight without foam

5.51 lbs. (2.5 kg)

### Total Depth

6.00" (15.2 cm)

### Buoyancy Max.

30 lbs.  
(13.61 kg)

Personalized Nameplate Available

## 1450 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- MIL C-4150J • Def Stan 81-41/STANAG 4280

## 1450 Case Accessories

Cat. #	Description	Sug. Retail
1450PF	Special Application Panel Frame	US\$21.95
1451	3 pc. Replacement Foam Set	US\$43.95
1453	Replacement O-ring	US\$4.70
1455	Padded Divider Set Only	US\$75.95

### Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
e-mail: [sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)