Uncontrolled document as of November 25, 2010. Refer to website for up to date specifications.







- Specifically designed in conjunction with Fire department and EMS personnel
- Lockable compartment for controlled substances
- Adjustable tray dividers allow for easy customization
- Sharps storage bracket included
- Top lid opens up to 180° for on-the-field anti-roll stability when open
- O-ring seal for dust and water resistant seal (IP66)
- Easy open Double Throw latches
- Open cell core with solid wall design strong, light weight
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded handles
- Stainless steel hardware and padlock protectors
- Personalized nameplate service available
- Lifetime Guarantee of Excellence

(Tray system not covered by lifetime warranty)

Each tray has an overall internal dimension of: 17" x 7.65" x 1.36" (43.18 x 19.43 x 3.45cm) LxWxD

**Total Depth** 

10.92" (27.7 cm)

**Buoyancy Max.** 

Also available with without EMS Organizer and Dividers

## 1460EMS Case Configurations

Cat. # Description
1460EMS 1460EMS Case

Interior Dimensions (L x W x D)

18.54" x 9.92" x 10.92" (47.1 x 25.2 x 27.7 cm)





**Bottom Depth** 

6.01" (15.3 cm)

lbs. (0 kg)

Weight without foam

## **1460EMS Case Specifications**

Exterior Dimensions (L x W x D)

20.85" x 12.73" x 12.75" (52.9 x 32.3 x 32.4 cm)

Lid Depth

4.91" (12.5 cm)

Weight with foam

18.2 lbs. (8.26 kg)

Range Temperature

-40 / 210° F (-40 / 99° C)

## 1460EMS Case Certificates

• IP66

## **1460EMS Case Accessories**

Cat. # Description Sug. Retail

1463 Replacement O-ring US\$5.50